

SPTK-740

Mini FTTX Fusion Splicer



Features

- Compact & Light weight
- Applied for Fibers, Cables and SOC (splice- on connector)
- Integrated Holder Design
- Fully Automatic, Semi-automatic and Manual Operation
- Shockproof, Drop resistance
- Power saving Function
- 4.3 inch Color LCD monitor
- USB&DC interface

Specification

Item	Parameters
Applicable fibers	SM, MM, DS, NZ-DS(G655), EDF, Bending Loss Insensitive fiber(G657), Pigtail, Drop cable and connector.
Fiber cleaved length	8-22mm
Average splice loss	0.02dB(SM)、0.01dB(MM)、0.04dB(DS)、0.04dB(NZDS)
Return loss	≥60dB



Tension test	2.0N(200gf)(Standard)
Protection sleeve length	20mm, 40mm, 60mm
Splice Program	5 groups of preset programs, 75 group of manual setting
Language	English, Chinese, Russian, Spanish, Portuguese.
Environment conditions	-25~+50℃ (operation temperature), 0~95%RH (humidity), 0~5000m (altitude)
Storage environment	-40~ +80℃ (temperature) , 0~95%RH (humidity)
Power supply	AC adaptor: 85~260V input voltage Internal battery: 12V, 6Ah, up to 260 times of continuous splice and heat
Dimensions/Weight	142 (D) ×122 (W) ×138 (H) mm/1.95kg

Standard Packages

- SPTK-740 Fusion Splicer
- Fiber Cleaver
- Drop Cable Stripper
- Connector holder
- Heater Device for Connector
- Spare Electrodes
- Charger
- Cooling Tray
- Manual Instruction
- Carry Box/ Bag

Note: If you need more customized services, please contact us.

E-mail: info@sopto.com.cn

Web : <http://www.sopto.com.cn>